Chemical Safety Data Sheet MSDS / SDS

Chromium(VI) oxide

Revision Date:2025-02-01 Revision Number:1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name	: Chromium(VI) oxide	
CBnumber	: CB5304358	
CAS	: 1333-82-0	
EINECS Number	: 215-607-8	
Synonyms	: CrO3,chromium(VI) oxide	
Relevant identified uses of the substance or mixture and uses advised against		

: For R&D use only. Not for medicinal, household or other use.
: none
: Chemicalbook
: Building 1, Huihuang International, Shangdi 10th Street, Haidian District, Beijing
: 010-86108875

SECTION 2: Hazards identification

GHS Label elements, including precautionary statements

```
Symbol(GHS)
```

Signal word

Danger

Precautionary statements

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P371+P380+P375 in case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

P320 Specific treatment is urgent (see ... on this label).

P308+P313 IF exposed or concerned: Get medical advice/attention.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continuerinsing.

P304+P340 IF INHALED: Remove victim to fresh air and Keep at rest in a position comfortable for breathing.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower.

P284 Wear respiratory protection.

P283 Wear fire/flame resistant/retardant clothing.		
P280 Wear protective gloves/protective clothing/eye protection/face protection.		
P260 Do not breathe dust/fume/gas/mist/vapours/spray.		
P221 Take any precaution to avoid mixing with combustibles/		
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.		
P201 Obtain special instructions before use.		
Hazard statements		
H318 Causes serious eye damage		
H330 Fatal if inhaled		
H410 Very toxic to aquatic life with long lasting effects		
H400 Very toxic to aquatic life		
H372 Causes damage to organs through prolonged or repeated exposure		
H361 Suspected of damaging fertility or the unborn child		
H350 May cause cancer		
H340 May cause genetic defects		
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled		
H317 May cause an allergic skin reaction		
H314 Causes severe skin burns and eye damage		
H310 Fatal in contact with skin		
H301 Toxic if swalloed		
H271 May cause fire or explosion; strong oxidiser		

SECTION 3: Composition/information on ingredients

Substance

Product name	: Chromium(VI) oxide
Synonyms	: CrO3,chromium(VI) oxide
CAS	: 1333-82-0
EC number	: 215-607-8
MF	: CrO3
MW	: 99.99

SECTION 4: First aid measures

Description of first aid measures

General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor

lf inhaled

After inhalation: fresh air. Immediately call in physician. If breathing stops: immediately apply artificial respiration, if necessary also oxygen.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

If swallowed

If swallowed: give water to drink (two glasses at most). Seek medical advice immediately. In exceptional cases only, if medical care is not available within one hour, induce vomiting (only in persons who are wide awake and fully conscious), administer activated charcoal (20 - 40 g in a 10% slurry) and consult a doctor as quickly as possible. Do not attempt to neutralise.

Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Chromium oxides Not combustible.

Has a fire-promoting effect due to release of oxygen. Ambient fire may liberate hazardous vapours.


Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Prevent fire extinguishing water from contaminating surface water or the ground water system.

NFPA 704



Short exposure could cause serious temporary or moderate residual injury (e.g. <u>liquid hydrogen, sulfuric acid, calcium</u> <u>hypochlorite</u>, hexafluorosilicic acid)

Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete,

FIRE 0 stone, and sand. Materials that will not burn in air when exposed to a temperature of 820 °C (1,500 °F) for a period of 5 minutes.(e.g. Carbon tetrachloride)

П	SPEC.	OX
	HAZ.	07

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid generation and inhalation of dusts in all circumstances. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

Environmental precautions

Do not let product enter drains.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully. Dispose of properly. Clean up affected area. Avoid generation of dusts.

Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.

Conditions for safe storage, including any incompatibilities

Storage conditions

Tightly closed. Keep locked up or in an area accessible only to qualified or authorized persons. Separately or together with other oxidising substances only and away from sources of ignition and heat. Because of their oxidation potential these products can raise the burning rate of combustible substances substantially or ignite combustible substances on contact with them. hygroscopic Heat sensitive.

Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

control parameter

Hazard composition and occupational exposure limits

Does not contain substances with occupational exposure limits.

Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly

fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Full contact

Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: 480 min

Material tested:KCL 741 Dermatril? L

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact Material: Nitrile rubber

Minimum layer thickness: 0,11 mm Break through time: 480 min

Material tested:KCL 741 Dermatril? L

Body Protection

Acid-resistant protective clothing

Respiratory protection

required when dusts are generated.

Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other

accompanying standards relating to the used respiratory protection system.

Recommended Filter type: Filter type P3

The entrepeneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains.

Information on basic physicochemical properties

Appearance	dark red powder, flakes
Odour	odorless
Odour Threshold	Not applicable
pН	< 1 at 100 g/l at 20 °C
Melting point/freezing point	Melting point/range: 196 °C - dec.
Initial boiling point and boiling range	330 °C
Flash point	Not applicable
Evaporation rate	No data available
Flammability (solid, gas)	The product is not flammable Test N.1: Test method for readily combustible solids
Upper/lower flammability or explosive	No data available
limits	
Vapour pressure	Not applicable
Vapour pressure Vapour density	Not applicable Not applicable
Vapour density	Not applicable
Vapour density Relative density	Not applicable 2,7 g/cm3 at 20 °C ca.2,7 - OECD Test Guideline 109
Vapour density Relative density Water solubility	Not applicable 2,7 g/cm3 at 20 °C ca.2,7 - OECD Test Guideline 109 ca.1.667 g/l - Regulation (EC) No. 440/2008, Annex, A.6- soluble
Vapour density Relative density Water solubility Partition coefficient: n-octanol/water	Not applicable 2,7 g/cm3 at 20 °C ca.2,7 - OECD Test Guideline 109 ca.1.667 g/l - Regulation (EC) No. 440/2008, Annex, A.6- soluble Not applicable for inorganic substances
Vapour density Relative density Water solubility Partition coefficient: n-octanol/water Autoignition temperature	Not applicable 2,7 g/cm3 at 20 °C ca.2,7 - OECD Test Guideline 109 ca.1.667 g/l - Regulation (EC) No. 440/2008, Annex, A.6- soluble Not applicable for inorganic substances not auto-flammable
Vapour density Relative density Water solubility Partition coefficient: n-octanol/water Autoignition temperature Decomposition temperature	Not applicable 2,7 g/cm3 at 20 °C ca.2,7 - OECD Test Guideline 109 ca.1.667 g/l - Regulation (EC) No. 440/2008, Annex, A.6- soluble Not applicable for inorganic substances not auto-flammable above melting point
Vapour density Relative density Water solubility Partition coefficient: n-octanol/water Autoignition temperature Decomposition temperature Viscosity	Not applicable 2,7 g/cm3 at 20 °C ca.2,7 - OECD Test Guideline 109 ca.1.667 g/l - Regulation (EC) No. 440/2008, Annex, A.6- soluble Not applicable for inorganic substances not auto-flammable above melting point Viscosity, kinematic: No data available Viscosity, dynamic: No data available

Other safety information

Relative vapor density

Not applicable

SECTION 10: Stability and reactivity

Reactivity

No data available

Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

Possibility of hazardous reactions

Risk of explosion with:

organic combustible substances Alkali metals

Ammonia nonmetals

halogen-halogen compounds hydrazine and derivatives nitrates

Reducing agents Nitric acid

Conditions to avoid

no information available

Incompatible materials

No data available

Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - 52 mg/kg (OECD Test Guideline 401) Acute toxicity estimate Inhalation - 0,051 mg/l (Expert judgment) Acute toxicity estimate Dermal - 300,1 mg/kg (Expert judgment) Skin corrosion/irritation Skin - Rabbit Result: Corrosive - 0,5 h Remarks: (ECHA) Serious eye damage/eye irritation Eyes - Rabbit Result: Causes burns. Remarks: (ECHA) Causes serious eye damage. Respiratory or skin sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled. Patch test: - Human Result: positive Remarks: (IUCLID) May cause an allergic skin reaction. Germ cell mutagenicity Remarks: (IUCLID) Carcinogenicity No data available **Reproductive toxicity** Suspected of damaging fertility. Specific target organ toxicity - single exposure May cause respiratory irritation. - Respiratory system Specific target organ toxicity - repeated exposure Inhalation - Causes damage to organs through prolonged or repeated exposure. No data available

Toxicity

SECTION 12: Ecological information

Toxicity

Toxicity to fish

LC50 - Pimephales promelas (fathead minnow) - 33,2 mg/l - 96 h Remarks: (in analogy to similar products) (ECHA)

Toxicity to daphnia and other aquatic invertebrates

EC50 - Daphnia magna (Water flea) - 0,035 mg/l - 48 h Remarks: (ECHA)

Persistence and degradability

The methods for determining the biological degradability are not applicable to inorganic substances.

Bioaccumulative potential

No data available

Mobility in soil

No data available

Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Other adverse effects

No data available

SECTION 13: Disposal considerations

Waste treatment methods

Product

See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

Incompatibilities

Chromium trioxide is a strong oxidizer. The solution in water is a strong acid. Reacts violently with bases and is corrosive. Contact with

reducing agents; fuels, organic chemicals, flammable and combustible materials, causing fire and explosion hazard. This chemical

decomposes above 250C to chromic oxide and oxygen with increased fire hazard. Attacks metals in the presence of moisture.

Waste Disposal

Reduce to Cr(III). If material cannot be recovered and recycled, dispose of sludge in a chemical waste landfill.

SECTION 14: Transport information

UN number

ADR/RID: 1463 IMDG: 1463 IATA: 1463

UN proper shipping name

	ADR/RID: CHROMIUM TRIOXIDE, ANHYDROUS IMDG: CHROMIUM TRIOXIDE,		
	ANHYDROUS		
IATA: Chromium trioxide,			
anhydrous			
14.3	Transport hazard class(es) ADR/RID: 5.1 (6.1, 8) IMDG: 5.1 (6.1, 8)	IATA: 5.1 (6.1)(8)	
14.4	Packaging group		
14.5	ADR/RID: II IMDG: II Environmental hazards	iata: II	
	ADR/RID: yes IMDG Marine pollutant: yes	IATA: no	
14.6	Special precautions for user		
	No data available		

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulations on the Safety Management of Hazardous Chemicals

China Catalog of Hazardous chemicals 2015:Listed. website: https://www.mem.gov.cn/

Measures for Environmental Management of New Chemical Substances

Korea Existing Chemicals List (KECL):Listed. website: http://ncis.nier.go.kr

Philippines Inventory of Chemicals and Chemical Substances (PICCS):Listed. website: https://emb.gov.ph/

Vietnam National Chemical Inventory:Listed. website: https://chemicaldata.gov.vn/

European Inventory of Existing Commercial Chemical Substances (EINECS):Listed. website: https://echa.europa.eu/

EC Inventory:Listed.

Chinese Chemical Inventory of Existing Chemical Substances (China IECSC):Listed. website: https://www.mee.gov.cn/

New Zealand Inventory of Chemicals (NZIoC):Listed. website: https://www.epa.govt.nz/

United States Toxic Substances Control Act (TSCA) Inventory:Listed. website: https://www.epa.gov/

SECTION 16: Other information

Abbreviations and acronyms

CAS: Chemical Abstracts Service

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

RID: Regulation concerning the International Carriage of Dangerous Goods by Rail

IMDG: International Maritime Dangerous Goods

IATA: International Air Transportation Association

TWA: Time Weighted Average

STEL: Short term exposure limit

LC50: Lethal Concentration 50%

LD50: Lethal Dose 50%

EC50: Effective Concentration 50%

References

[1] CAMEO Chemicals, website: http://cameochemicals.noaa.gov/search/simple

[2] ChemlDplus, website: http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp

[3] ECHA - European Chemicals Agency, website: https://echa.europa.eu/

[4] eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website:

http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en

[5] ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: http://www.phmsa.dot.gov/hazmat/library/erg

[6] Germany GESTIS-database on hazard substance, website: http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp

[7] HSDB - Hazardous Substances Data Bank, website: https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm

[8] IARC - International Agency for Research on Cancer, website: http://www.iarc.fr/

[9] IPCS - The International Chemical Safety Cards (ICSC), website: http://www.ilo.org/dyn/icsc/showcard.home

[10] Sigma-Aldrich, website: https://www.sigmaaldrich.com/

Other Information

Do NOT take working clothes home. Rinse contaminated clothing with plenty of water because of fire hazard. The symptoms of asthma often do not become manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation are therefore essential. Anyone who has shown symptoms of asthma due to this substance should avoid all further contact. Depending on the degree of exposure, periodic medical examination is suggested.

Disclaimer:

The information in this MSDS is only applicable to the specified product, unless otherwise specified, it is not applicable to the mixture of this product and other substances. This MSDS only provides information on the safety of the product for those who have received the appropriate professional training for the user of the product. Users of this MSDS must make independent judgments on the applicability of this SDS. The authors of this MSDS will not be held responsible for any harm caused by the use of this MSDS.